



Model NO.: OBS-8804XKA / 8808XKA / 8816XKA / 8832XKA



Product specification :

1. Support ONVIF protocol, compatible with standard ONVIF IP cameras
2. Support P2P, Built-in free DDNS
3. High-performance CPU, support TV、VGA、HDMI simultaneously output.
4. Adopted H.264 video compression and G. 711 audio compression, can decoding HD resolution video
5. Graphic operation interface, support front panel、remote、mouse operation
6. Support varied video video reach,Local and network playback
7. Support varied network protocol, such asTCP/IP, UDP, RTP/RTSP, DHCP, PPPoE, DDNS, NTP
8. Support mobile phone remote monitoring

Parameters :

Model :	OBS-8804XKA	OBS-8808XKA	OBS-8816XKA	OBS-8832XKA
Operating system	Emberdded LINUX			
IPC input	4ch D1 / 4ch 720P /4ch 1080P@30fps	8ch D1 / 8ch 720P /8ch 1080P@30fps	16ch D1 / 16ch 720P / 8ch 1080P@30fps	32ch D1 / 22ch 720P / 16ch 1080P@30fps
protocol support	ONVIF Core Spec 2.2 Compatible with Standard ONVIF IP cameras			
Intercom	NO		1CH RCA Interface	
CVBS Output	1ch BNC (1.0Vp-p,75ohms)			
VGA Output	1ch ,resolution optional (1920x1080,1280x1024,1280x720,1024x768,800x600)			
HDMI Output	1ch, resolution optional(1920x1080,1280x1024,1280x720,1024x768,800x600)			
Audio output	1CH RCA Interface			
Video compression	H.264/MPEG 4 AVC, up to Main Profile 5.0			
Video resolution	5MP/3MP 1080p/960p/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF			
Video Frame Rate	1 ~ 30 frames			
Video bitrate	48Kbps~12288Kbps/			
Stream type	Composite audio stream			
Audio compression	G.711A			
Audio bitrate	64Kbps			
Local playback	4ch sync playback	8ch sync playback		16ch sync playback
mobile surveillance	Support Iphone,android,symbian,windows,blackberry			
DDNS, P2P	Support			
SATA interface	2HDD			
Network interface	1 RJ45 10M/100M adjust-automatically Ethernet interface		1 RJ45 10M/100M/1000M adjust-automatically Ethernet interface	
USB interface	2 USB2.0 high-speed interface			
Alarm input	4ch	8ch		16ch
Alarm output	1ch	3ch		3ch
RS-485	Support			
Dimension	1.5U 360*250*60mm			
installation	Desktop installation			
Power supply	DC 12V			
Working temperature	-10℃-- +55℃			
Working Humidity	10%--90%			
Dimension:				

