

H O M E & B U I L D I N G
Y A C H T A U T O M A T I O N
S E C U R I T Y S O L U T I O N

OBS-X1003W-X2003W-X4003W

Full HD IP IR waterproof camera




Key Specifications:

- Support the photosensitive resistance signal linkage ICR to switch on day and night;
- Intelligent 2D, 3D noise reduction algorithm, AE exposure algorithm, Clean and fresh night scene;
- Support H. 265 Main profile/h. 264 Main profile/M - JPEG coding, achieve lower stream and high-definition image quality;
- 3 stream output (optional 2ch H.265 / H.264 + 1ch MJPEG);
- Support Android、IOS mobile phone P2P interview;

Specification:

Module	OBS-X1003W	OBS-X2003W	OBS-X4003W
Sensor	1/4-inch 1.0 Megapixel OV9712+HI3518E CMOS	1/2.7-inch 2.0 Megapixel SC2035+3516C CMOS	1/3-inch 4.0 Megapixel OV4689+3516D H.265 CMOS
Resolution	HD: 720p/30fps, 720p/25fps	HD: 1080p/30fps, 1080p/25fps	HD:2592x1520/28fps,2592x1520/ 22fps or 5MP-2592x1944@15fps
IR range	15M (36pcs IR leds)		
IR control	auto		
Steam	triple streaming, 2 H.264 & 1 MJPEG or triple streaming, H.264+H.265 & 1 MJPEG		
Lens	Fix lens 3.6MM		
Compression	H.264/H.265M-JPEG		
P2P	android、Iphone		



H O ME & B UILDING YACHT AUTOMATION S ECURITY SOLUTION

Protocol	TCP/IP , HTTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P ,
Power	DC12V(2A)
Temperature	-15℃ ~ +60℃
Consumption	≤10W
Connector	RJ45
Thunder Proof	6000V